
REMA TIP TOP GmbH

Revision date: 21.08.2007 Revision no.: 1,14



00156-0009



## 1. Identification of the substance/preparation and of the company/undertaking

#### Identification of the substance or preparation

TIP TOP CLEANING SOLVENT R4, free of chlorinated and aromatic hydrocarbons

Art.-No.:

595 9118, 595 9125, 595 9132, 595 9156

Use of the substance/preparation

Cleaning agent

Company/undertaking identification

REMA TIP TOP GmbH a company of the group Stahlgruber Otto Gruber GmbH & Co KG

Gruber Straße 63

D-85586 Poing

Gruber Straße 65

D-85586 Poing

Telephone ++49 (0) 8121 / 707 - 0

Inquiry office

Emergency telephone: ++49 (0) 6132 / 84463 (GBK Gefahrgut Buero GmbH, Ingelheim)

Responsible for the safety data sheet: sds@gbk-ingelheim.de

#### 2. Hazards identification

#### Classification

Indications of danger: Highly flammable, Harmful, Dangerous for the environment

R-phrases:

Highly flammable.

Irritating to eyes and skin.

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Harmful: may cause lung damage if swallowed. Vapours may cause drowsiness and dizziness.

#### 3. Composition/information on ingredients

## Chemical characterization

(preparation)

Preparation solved in petroleum spirit

## **Hazardous components**

EC-No.	CAS-No.	Chemical name	Quantity	Classification
205-500-4	141-78-6	Ethyl acetate	< 75 %	F, Xi R11-36-66-67
295-529-9	92062-15-2	Solvent naphta (petroleum)	< 35 %	F, Xn, Xi, N R11-38-51-53-65-67

Full text of each relevant R phrase can be found in heading 16.

## **Further Information**

According to note P to the directive 67/548/EEC, "Solvent naphta (petroleum)" is not to be classified as "carcinogenic" ingredient because a benzene content (EINECS No. 200-753-7) is below 0.1 % by weight.

## 4. First aid measures

## **General information**

Remove contaminated soaked clothing immediately.

In the event of persistent symptoms receive medical treatment.

Take away from danger area and lay down affected person.

GB - EN Page 1 of 7

REMA TIP TOP GmbH

Revision date: 21.08.2007 Revision no.: 1.14



00156-0009



#### After inhalation

Move to fresh air in case of accidental inhalation of vapours.

If you feel unwell, seek medical advice.

#### After contact with skin

Wash off with soap and plenty of water.

Treat subsequently with skin cream.

Consult a doctor if skin irritation persists.

#### After contact with eyes

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.

Consult a physician.

#### After ingestion

Induce vomiting only upon the advice of a physician.

Attention. Beware, danger of aspiration.

Do not induce vomiting.

Summon a doctor immediately.

## 5. Fire-fighting measures

## Suitable extinguishing media

Alcohol-resistant foam, dry chemical, carbon dioxide (CO2), water-spray.

## Extinguishing media which must not be used for safety reasons

Full water jet

# Special exposure hazards arriving from substance or preparation itself, combustion products, resulting gases

Fire may produce:

Carbon monoxide and carbon dioxide.

## Special protective equipment for fire-fighters

Use breathing apparatus with independent air supply.

Protective suit

## **Additional information**

Vapours are heavier than air and spread along ground.

The vapour/air mixture is explosive, even in empty, uncleaned receptacles.

Cool containers at risk with water spray jet.

Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

## 6. Accidental release measures

## **Personal precautions**

In case of vapour formation use respirator.

Use only explosion-proof equipment.

Avoid contact with skin, eyes and clothing.

Ensure adequate ventilation.

Remove persons to safety.

Keep away sources of ignition.

## **Environmental precautions**

Do not discharge into the drains/surface waters/groundwater.

# Methods for cleaning up/taking up

Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder).

Shovel into suitable container for disposal.

GB - EN Page 2 of 7

REMA TIP TOP GmbH

Revision date: 21.08.2007 Revision no.: 1,14



00156-0009



## 7. Handling and storage

## **Handling**

## Advice on safe handling

Keep container tightly closed.

Vapours are heavier than air and spread along ground.

Use only in thoroughly ventilated areas.

Avoid contact with skin, eyes and clothing.

# Advice on protection against fire and explosion

Do not smoke - volatile.

Keep away from heat and sources of ignition.

Take precautionary measures against static discharges.

Use only explosion-proof equipment.

#### Storage

#### Requirements for storage rooms and vessels

Keep container tightly closed in a dry, cool and well-ventilated place.

Pay attention to anti-explosion rules.

## Advice on storage compatibility

Incompatible with oxidizing agents.

#### Further information on storage conditions

Keep away from food, drink and animal feeding stuffs.

Storageclass (VCI)

3 A

## 8. Exposure controls/personal protection

## **Exposure limit values**

## **Exposure limits (EH40)**

CAS No.	Substance	ml/m³	mg/m³	F/ml	Category	Origin
141-78-6	Ethyl acetate	200	-		TWA (8 h)	WEL
	Ethyl acetate	400	-		STEL (15 min)	WEL

## **Exposure controls**

## Occupational exposure controls

Ensure adequate ventilation, especially in confined areas.

# Protective and hygiene measures

Do not inhale vapours.

Wash hands before breaks and immediately after handling the product.

When using, do not eat, drink or smoke.

Treat subsequently with skin cream.

Remove and wash contaminated clothes before re-use.

# Respiratory protection


In case of insufficient ventilation wear suitable respiratory equipment (gas filter type A).

#### **Hand protection**

GB - EN Page 3 of 7

REMA TIP TOP GmbH

Revision date: 21.08.2007 Revision no.: 1,14



00156-0009



Splash protection:

Protective gloves resistant to chemicals made off butyl, Minimum coat thickness 0,7 mm, Permeation resistance (wear duration) approx. 120 minutes, i.e. protective glove <Butoject 898> made by www.kcl.de. Protective gloves resistant to chemicals made off nitrile, Minimum coat thickness 0.4 mm, Permeation resistance (wear duration) approx. 30 minutes, i.e. protective glove <Camatril Velours 730> made by www.kcl.de.

This recommendation refers exclusively to the chemical compatibility and the lab test conforming to EN 374 carried out under lab conditions.

Requirements can vary as a function of the use. Therefore it is necessary to adhere additionally to the recommendations given by the manufacturer of protective gloves.

#### Eye protection

Eye wash bottle with pure water.

Tightly fitting goggles

## Skin protection

Solvent-resistant apron.

## 9. Physical and chemical properties

## **General information**

Physical state Liquid
Colour Colourless
Odour Fruity

## Important health, safety and environmental information

Test method

Changes in the physical state

Melting point <- 20 °C

Boiling point 76 °C approx.

Flash point < - 4 °C

Flammability

Lower explosion limits 0,6 vol. %

Upper explosion limits

Ignition temperature 460 °C
Vapour pressure: 102 hPa

at (20 °C)

Density (at 20 °C): 0,86 g/cm³
Water solubility: Immiscible / 7,7 g/L

at (20 °C)

Flow time : < 30 s 3 DIN/ISO 2431

## Solvent content

100 %

Löslichkeit/Wasser-Bemerkung:

#### 10. Stability and reactivity

#### Conditions to avoid

To avoid thermal decomposition, do not overheat.


Vapour/air mixtures are explosive at intensive warming.

Heating can release vapours which can be ignited.

GB - EN Page 4 of 7

REMA TIP TOP GmbH

Revision date: 21.08.2007 Revision no.: 1,14



00156-0009



#### Materials to avoid

Oxidizing agents.

## **Hazardous decomposition products**

Carbon monoxide and carbon dioxide.

#### Additional information

No decomposition if stored and applied as directed.

## 11. Toxicological information

## Empirical data on effects on humans

Irritating to eyes and skin.

Vapours may cause drowsiness and dizziness.

Harmful: may cause lung damage if swallowed.

Inhalation of high vapour concentration may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhoea.

Repeated or prolonged exposure may cause skin irritation and dermatitis, due to degreasing properties of the product.

## 12. Ecological information

#### **Further information**

Do not flush into surface water or sanitary sewer system.

Slightly water hazardous.

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

## 13. Disposal considerations

## Advice on disposal

Where possible recycling is preferred to disposal.

Can be incinerated, when in compliance with local regulations.

#### Waste disposal number of waste from residues/unused products

080117 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF

COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU and removal of paint and varnish; wastes from paint or varnish removal containing organic solvents or other dangerous substances

Classified as hazardous waste.

# Contaminated packaging

Empty containers should be taken for local recycling, recovery or waste disposal.

Contaminated packaging should be emptied as far as possible and after appropriate cleansing may be taken for reuse.

Packaging that cannot be cleaned should be disposed of like the product.

#### **14. Transport information**


## **Land transport (ADR/RID)**

ADR/RID class	3
Classification code :	F1
Hazard-no.	33
UN number	1263
Hazard label	3

GB - EN Page 5 of 7

REMA TIP TOP GmbH

Revision date: 21.08.2007 Revision no.: 1,14



00156-0009

TO P

ADR/RID packing group II
Limited quantity LQ 6

## **Description of the goods**

Paint related material

## Remarks (land transport)

LQ 6: combination packaging: 5 I / 30 kg (total gross mass); trays: 1 I / 20 kg (total gross mass).

## **Inland waterways transport**

## **Marine transport**

 IMDG code
 3

 UN number
 1263

 Marine pollutant
 No

 EmS
 F-E; S-E

 IMDG packing group
 II

Limited quantity: 5 L / 30 kg

Hazard label 3

## Description of the goods

PAINT RELATED MATERIAL

#### Remarks (marine transport)

Limited quantities (section 3.4): combination packaging: 5 I / 30 kg (total gross mass); trays: 5 I / 20 kg (total gross mass).

#### Air transport

ICAO/IATA-DGR 3 UN/ID number 1263 Hazard label 3 IATA-packing instructions - Passenger 305 IATA-max. quantity - Passenger 5 L IATA-packing instructions - Cargo 307 IATA-max. quantity - Cargo 60 L ICAO packing group Ш

Limited quantity Passenger Y305 / 1 L

# **Description of the goods**

PAINT RELATED MATERIAL

## 15. Regulatory information

# **Labelling**

Indication of danger F - Highly flammable; Xn - Harmful; N - Dangerous for the environment Additional advice on labelling According to EC-regulations the product is to be labelled as follows:

#### Hazardous component(s) to be indicated on label

Solvent naphta (petroleum)

## R phrases

11 Highly flammable.

Harmful: may cause lung damage if swallowed.
Vapours may cause drowsiness and dizziness.

36/38 Irritating to eyes and skin.

51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

## S phrases

16 Keep away from sources of ignition - No smoking.

GB - EN Page 6 of 7

REMA TIP TOP GmbH

Revision date: 21.08.2007 Revision no.: 1,14



TIP TOP CLEANING SOLVENT R4, free of chlorinated and aromatic hydrocarbons 00156-0009

23	Do not breathe vapour.
26	In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
33	Take precautionary measures against static discharges.
35	This material and its container must be disposed of in a safe way.
61	Avoid release to the environment. Refer to special instructions / Safety data sheets.
62	If swallowed, do not induce vomiting: seek medical advice immediately and show this container
	or label.

## **National regulatory information**

Employment restrictions Observe employment restrictions for young people.; Observe employment restrictions for child bearing mothers and nursing.

Water contaminating class 1 - slightly water contaminating

1999/13/EC (VOC) 100 %

## 16. Other information

## Full text of R-phrases referred to under sections 2 and 3

11	Highly flammable.
36	Irritating to eyes.
38	Irritating to skin.
51	Toxic to aquatic organisms.
53	May cause long-term adverse effects in the aquatic environment.
65	Harmful: may cause lung damage if swallowed.
66	Repeated exposure may cause skin dryness or cracking.
67	Vapours may cause drowsiness and dizziness.
36/38	Irritating to eves and skin.

51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

## Other data

Data of items 4 to 8, as well as 10 to 12, do partly not refer to the use and the regular employing of the product (in this sense consult information on use and on product), but to liberation of major amounts in case of accidents and irregularities.

The information describes exclusively the safety requirements for the product (s) and is based on the present level of our knowledge.

The delivery specifications are contained in the corresponding product sheet.

This data does not constitute a guarantee for the characteristics of the product(s) as defined by the legal warranty regulations.

"(n.a. = not applicable; n.d. = not determined)"

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)

GB - EN Page 7 of 7