

Page 1 of 11 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revised on / Version: 16.08.2013 / 0005 Replaces revision of / Version: 13.05.2013 / 0004 Valid from: 16.08.2013 PDF print date: 20.08.2013 Leichtlauf High Tech 5W-40 205 L Art.: 3869

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

(GB)

Leichtlauf High Tech 5W-40 205 L Art.: 3869

1.2 Relevant identified uses of the substance or mixture and uses advised against Relevant identified uses of the substance or mixture:

Uses advised against:

No information available at present.

1.3 Details of the supplier of the safety data sheet

LIQUI MOLY GmbH, Jerg-Wieland-Straße 4, D-89081 Ulm-Lehr Telephone: (+49) 0731-1420-0, Fax: (+49) 0731-1420-88

E-mail address of the competent person: info@chemical-check.de, k.schnurbusch@chemical-check.de

1.4 Emergency telephone

Emergency information services / official advisory body:

Telephone number of the company in case of emergencies:

Tel.: (+49) 0731-1420-0

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

2.1.1 Classification according to Regulation (EC) 1272/2008 (CLP) The mixture is not classified as dangerous in the terms of the Regulation (EC) 1272/2008 (CLP).

2.1.2 Classification according to Directives 67/548/EEC and 1999/45/EC (including amendments)

The mixture is not classified as dangerous in the terms of the directive 1999/45/EC.

2.2.1 abol elements

2.2 Label elements

2.2.1 Labeling according to Regulation (EC) 1272/2008 (CLP)

EUH208-Contains Calcium alkyl aryl sulfonate, long-chain. May produce an allergic reaction. EUH210-Safety data sheet available on request.

2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006.

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006.

Product can compose a film on the water surface, which can prevent oxygen exchange. Hazardous to drinking water, on escape of even small quantities.

SECTION 3: Composition/information on ingredients



Page 2 of 11

œ

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revised on / Version: 16.08.2013 / 0005 Replaces revision of / Version: 13.05.2013 / 0004 Valid from: 16.08.2013 PDF print date: 20.08.2013 Leichtlauf High Tech 5W-40 205 L Art.: 3869

3.1 Substance

n.a. 3.2 Mixture

3.2 WIXture	
Distillates (petroleum), hydrotreated heavy paraffinic	
Registration number (REACH)	
Index	649-467-00-8
EINECS, ELINCS, NLP	265-157-1
CAS	CAS 64742-54-7
content %	30-60
Classification according to Directive 67/548/EEC	
Classification according to Regulation (EC) 1272/2008 (CLP)	Asp. Tox. 1, H304
Phenol, 2,2'-Polythiobis[4-C8-30-alkyl derivative, over-alkaline calcium	
salts	
Registration number (REACH)	01-2119524004-56-XXXX
Index	
EINECS, ELINCS, NLP	291-829-9
CAS	CAS 90480-91-4
content %	1-5
Classification according to Directive 67/548/EEC	Dangerous for the environment, R53
Classification according to Regulation (EC) 1272/2008 (CLP)	Aquatic Chronic 4, H413
Polyolefin polyamine succinimide, Polyol	
Registration number (REACH)	
Index	
EINECS, ELINCS, NLP	-
CAS	CAS 147880-09-9
content %	1-<5
Classification according to Directive 67/548/EEC	Dangerous for the environment, R53
Classification according to Regulation (EC) 1272/2008 (CLP)	Aquatic Chronic 4, H413
Phosphorodithioic acid, mixed O,O-bis(sec-Bu and 1,3-dimethylbutyl)	
esters, zinc salts	
Registration number (REACH)	01-2119657973-23-XXXX
Index	
EINECS, ELINCS, NLP	272-238-5
CAS	CAS 68784-31-6
content %	1-<2,5
Classification according to Directive 67/548/EEC	Irritant, Xi, R41
	Dangerous for the environment, N, R51
	Dangerous for the environment, R53
Classification according to Regulation (EC) 1272/2008 (CLP)	Eye Dam. 1, H318
	Aquatic Chronic 2, H411

For the text of the R-phrases / H-phrases and classification codes (GHS/CLP), see Section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures Inhalation

Remove person from danger area.

Supply person with fresh air and consult doctor according to symptoms.

Skin contact

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

Eye contact

Remove contact lenses.

Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

Ingestion



Page 3 of 11 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revised on / Version: 16.08.2013 / 0005 Replaces revision of / Version: 13.05.2013 / 0004 Valid from: 16.08.2013 PDF print date: 20.08.2013 Leichtlauf High Tech 5W-40 205 L Art.: 3869

Rinse the mouth thoroughly with water. Call doctor immediately - have Data Sheet available.

4.2 Most important symptoms and effects, both acute and delayed

Irritation of the eyes With long-term contact: Drying of the skin. Dermatitis (skin inflammation) Sensitive individuals: Allergic reaction possible. With oil mist formation: Irritation of the respiratory tract In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours. **4.3 Indication of any immediate medical attention and special treatment period**

4.3 Indication of any immediate medical attention and special treatment needed

n.c.

(GB)

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

CO2 Foam Dry extinguisher Large fire: Water jet spray / alcohol resistant foam Cool container at risk with water.

Unsuitable extinguishing media

High volume water jet

5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop: Oxides of carbon Oxides of nitrogen Oxides of phosphorus Toxic pyrolysis products. Hot product gives off combustible vapours.

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Protective respirator with independent air supply. According to size of fire Full protection, if necessary Dispose of contaminated extinction water according to official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Avoid formation of oil mist. Remove possible causes of ignition - do not smoke. Avoid contact with eyes or skin. If applicable, caution - risk of slipping

6.2 Environmental precautions

If leakage occurs, dam up.

Resolve leaks if this possible without risk.

Prevent from entering drainage system.

Prevent surface and ground-water infiltration, as well as ground penetration. If accidental entry into drainage system occurs, inform responsible authorities.

6.3 Methods and material for containment and cleaning up

Soak up with absorbent material (e.g. universal binding agent, sand, diatomaceous earth) and dispose of according to Section 13. Oil binder

6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.



Page 4 of 11

(GB)

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revised on / Version: 16.08.2013 / 0005 Replaces revision of / Version: 13.05.2013 / 0004 Valid from: 16.08.2013 PDF print date: 20.08.2013 Leichtlauf High Tech 5W-40 205 L Art.: 3869

SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

7.1 Precautions for safe handling

7.1.1 General recommendations

Avoid formation of oil mist.

Avoid contact with eyes.

Avoid long lasting or intensive contact with skin.

Do not heat to temperatures close to flash point.

Eating, drinking, smoking, as well as food-storage, is prohibited in work-room. Do not carry cleaning cloths soaked in product in trouser pockets.

Observe directions on label and instructions for use.

7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

7.2 Conditions for safe storage, including any incompatibilities

Not to be stored in gangways or stair wells.

Store product closed and only in original packing. Protect against moisture and store closed. Store at room temperature.

7.3 Specific end use(s)

No information available at present.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Chemical Name	Oil mist, mineral				Content %:
WEL-TWA: 5 mg/m3 (ACGIH)		WEL-STEL:	10 mg/m3 (ACGIH	1)	
BMGV:				Other information:	

WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.

** = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.

Distillates (petroleum), hydrotreated heavy paraffinic									
Area of application	Exposure route / Environmental	Effect on health	Descriptor	Value	Unit	Note			
	compartment								
Workers / employees	Human - inhalation	Long term, local effects	DNEL	5,4	mg/m3				
Consumer	Human - inhalation	Long term, local effects	DNEL	1,2	mg/m3				
	Environment - oral (animal feed)		PNEC	9,33	mg/kg feed				

8.2 Exposure controls

8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction. If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn. Applies only if maximum permissible exposure values are listed here.

8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.



Page 5 of 11 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revised on / Version: 16.08.2013 / 0005 Replaces revision of / Version: 13.05.2013 / 0004 Valid from: 16.08.2013 PDF print date: 20.08.2013 Leichtlauf High Tech 5W-40 205 L Art.: 3869

Wash hands before breaks and at end of work. Keep away from food, drink and animal feedingstuffs. Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection: Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection: Protective gloves, oil resistant (EN 374) If applicable Protective nitrile gloves (EN 374) Permeation time (penetration time) in minutes: 480 Minimum layer thickness in mm: 0,4

Skin protection - Other: Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments)

Respiratory protection: Normally not necessary. With oil mist formation: Filter A2 P2 (EN 14387), code colour brown, white Observe wearing time limitations for respiratory protection equipment.

Thermal hazards:

(GB)

If applicable, these are included in the individual protective measures (eye/face protection, skin protection, respiratory protection).

Additional information on hand protection - No tests have been performed.

In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents. Selection of materials derived from glove manufacturer's indications.

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account. Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use. The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

8.2.3 Environmental exposure controls

No information available at present.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

of the second seco	
Physical state:	Liquid
Colour:	Brown
Odour:	Characteristic
Odour threshold:	Not determined
pH-value:	Not determined
Melting point/freezing point:	-33 °C
Initial boiling point and boiling range:	Not determined
Flash point:	236 °C
Evaporation rate:	Not determined
Flammability (solid, gas):	Not determined
Lower explosive limit:	Not determined
Upper explosive limit:	Not determined
Vapour pressure:	Not determined
Vapour density (air = 1):	Not determined
Density:	0,855 g/ml
Bulk density:	Not determined
Solubility(ies):	Not determined
Water solubility:	Insoluble
Partition coefficient (n-octanol/water):	Not determined
Auto-ignition temperature:	Not determined
Decomposition temperature:	Not determined



Page 6 of 11 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revised on / Version: 16.08.2013 / 0005 Replaces revision of / Version: 13.05.2013 / 0004 Valid from: 16.08.2013 PDF print date: 20.08.2013 Leichtlauf High Tech 5W-40 205 L Art.: 3869

Viscosity: Viscosity: Explosive properties: Oxidising properties:

(GB)

9.2 Other information

Miscibility: Fat solubility / solvent: Conductivity: Surface tension: Solvents content: 90 mm2/s (40°C) 14,7 mm2/s (100°C) Not determined Not determined

Not determined Not determined Not determined Not determined Not determined

SECTION 10: Stability and reactivity

10.1 Reactivity

See also Subsection 10.2 to 10.6. The product has not been tested.

10.2 Chemical stability

See also Subsection 10.1 to 10.6. Stable with proper storage and handling.

10.3 Possibility of hazardous reactions

See also Subsection 10.1 to 10.6. No decomposition if used as intended.

10.4 Conditions to avoid

See also section 7. Protect from humidity. Open flame, ignition sources

10.5 Incompatible materials

See also section 7. Avoid contact with strong oxidizing agents. **10.6 Hazardous decomposition products** See also Subsection 10.1 to 10.5. See also section 5.2

No decomposition when used as directed.

SECTION 11: Toxicological information

Possibly more information on health effects, see Section 2.1 (classification).

Toxicity/effect	Endpoin	Value	Unit	Organism	Test method	Notes
	t					
Acute toxicity, by oral route:						n.d.a.
Acute toxicity, by dermal route:						n.d.a.
Acute toxicity, by inhalation:						n.d.a.
Skin corrosion/irritation:						n.d.a.
Serious eye damage/irritation:						n.d.a.
Respiratory or skin sensitisation:						n.d.a.
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						n.d.a.
Reproductive toxicity:						n.d.a.
Specific target organ toxicity -						n.d.a.
single exposure (STOT-SE):						
Specific target organ toxicity -						n.d.a.
repeated exposure (STOT-RE):						
Aspiration hazard:						n.d.a.
Respiratory tract irritation:						n.d.a.
Repeated dose toxicity:						n.d.a.
Symptoms:						n.d.a.
Other information:						Classification accordi
						to calculation procedu



Page 7 of 11 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revised on / Version: 16.08.2013 / 0005 Replaces revision of / Version: 13.05.2013 / 0004 Valid from: 16.08.2013 PDF print date: 20.08.2013 Leichtlauf High Tech 5W-40 205 L Art.: 3869

(GB)

Distillates (petroleum), hydrotreated heavy paraffinic							
Toxicity/effect	Endpoin	Value	Unit	Organism	Test method	Notes	
	t						
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat			
Acute toxicity, by dermal route:	LD50	>5000	mg/kg	Rabbit			
Skin corrosion/irritation:						Not irritant	
Serious eye damage/irritation:						Not irritant	
Respiratory or skin sensitisation:						Not sensitizising	
Aspiration hazard:						Yes	

SECTION 12: Ecological information

Possibly more information on environmental effects, see Section 2.1 (classification).
Leichtlauf High Tech 5W-40 205 L

Toxicity/effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
Toxicity to fish:							n.d.a.
Toxicity to daphnia:							n.d.a.
Toxicity to algae:							n.d.a.
Persistence and							Isolate as much as
degradability:							possible with an oil
							separator.
Bioaccumulative							n.d.a.
potential:							
Mobility in soil:							n.d.a.
Results of PBT and							n.d.a.
vPvB assessment:							
Other adverse effects:							n.d.a.

Distillates (petroleum), hydrotreated heavy paraffinic									
Toxicity/effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes		
Persistence and							Not readily biodegradable		
degradability:									
Water solubility:							Insoluble		

Toxicity/effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
Toxicity to fish:	LC50		>1000	mg/l	Oncorhynchus mykiss		
Toxicity to daphnia:	EC50		>1000	mg/l	Daphnia magna		
Toxicity to algae:	ErC50		>1000	mg/l	Selenastrum capricornutum		
Toxicity to algae:	EbC50		>1000	mg/l	Selenastrum capricornutum		
Persistence and degradability:		28d	7,38	%			Not readily biodegradable

SECTION 13: Disposal considerations

13.1 Waste treatment methods

For the substance / mixture / residual amounts

Soaked polluted cloths, paper or other organic materials represent a fire hazard and should be controlled, collected and disposed of. EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product.

Owing to the user's specific conditions for use and disposal, other waste codes may be

allocated under certain circumstances. (2001/118/EC, 2001/119/EC, 2001/573/EC)

13 02 05 mineral-based non-chlorinated engine, gear and lubricating oils

Recommendation:

Pay attention to local and national official regulations Implement substance recycling.



Page 8 of 11 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revised on / Version: 16.08.2013 / 0005 Replaces revision of / Version: 13.05.2013 / 0004 Valid from: 16.08.2013 PDF print date: 20.08.2013 Leichtlauf High Tech 5W-40 205 L Art.: 3869

E.g. suitable incineration plant. Observe regulations for disposal of old oil/waste.

(GB)

For contaminated packing material Pay attention to local and national official regulations Empty container completely. Uncontaminated packaging can be recycled. Dispose of packaging that cannot be cleaned in the same manner as the substance. 15 01 01 paper and cardboard packaging 15 01 02 plastic packaging 15 01 04 metallic packaging

SECTION 14: Transport information

General statements	
UN number:	n.a.
Transport by road/by rail (ADR/RID)	
UN proper shipping name:	
Transport hazard class(es):	n.a.
Packing group:	n.a.
Classification code:	n.a.
LQ (ADR 2013):	n.a.
LQ (ADR 2009):	n.a.
Environmental hazards:	Not applicable
Tunnel restriction code:	
Transport by sea (IMDG-code)	
UN proper shipping name:	
Transport hazard class(es):	n.a.
Packing group:	n.a.
Marine Pollutant:	n.a
Environmental hazards:	Not applicable
Transport by air (IATA)	
UN proper shipping name:	
Transport hazard class(es):	n.a.
Packing group:	n.a.
Environmental hazards:	Not applicable
Special precautions for user	
Unless specified otherwise, general measures for safe transport n	nust be followed.
, 3, 3,,,, .	

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Non-dangerous material according to Transport Regulations.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture For classification and labelling see Section 2.

n.a.

Observe restrictions:

15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

SECTION 16: Other information

These details refer to the product as it is delivered. Revised sections:

2, 3, 8, 11, 12

Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP): Not applicable

The following phrases represent the posted R phrases / H phrases, Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).



Page 9 of 11 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revised on / Version: 16.08.2013 / 0005 Replaces revision of / Version: 13.05.2013 / 0004 Valid from: 16.08.2013 PDF print date: 20.08.2013 Leichtlauf High Tech 5W-40 205 L Art.: 3869

53 May cause long-term adverse effects in the aquatic environment.
41 Risk of serious damage to eyes.
51 Toxic to aquatic organisms.
H304 May be fatal if swallowed and enters airways.
H318 Causes serious eye damage.

H411 Toxic to aquatic life with long lasting effects.

(GB)

H413 May cause long lasting harmful effects to aquatic life.

Asp. Tox. — Aspiration hazard Aquatic Chronic — Hazardous to the aquatic environment - chronic Eye Dam. — Serious eye damage

Any abbreviations and acronyms used in this document:

AC Article Categories acc., acc. to according, according to ACGIH American Conference of Governmental Industrial Hygienists ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road) AOEL Acceptable Operator Exposure Level AOX Adsorbable organic halogen compounds approx. approximately Art., Art. no. Article number Acute Toxicity Estimate according to Regulation (EC) 1272/2008 (CLP) ATE BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany) Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany) BAuA BCF Bioconcentration factor Berufsgenossenschaftliche Vorschrift (= Accident Prevention Regulation) BGV Butylhydroxytoluol (= 2.6-Di-t-butyl-4-methyl-phenol) BHT BMGV Biological monitoring guidance value (EH40, UK) BOD Biochemical oxygen demand BSEF Bromine Science and Environmental Forum bw body weight CAS **Chemical Abstracts Service** CEC Coordinating European Council for the Development of Performance Tests for Fuels, Lubricants and Other Fluids CESIO Comité Européen des Agents de Surface et de leurs Intermédiaires Organiques CIPAC Collaborative International Pesticides Analytical Council CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures) CMR carcinogenic, mutagenic, reproductive toxic COD Chemical oxygen demand CTFA Cosmetic, Toiletry, and Fragrance Association DMEL Derived Minimum Effect Level DNEL Derived No Effect Level DOC Dissolved organic carbon DT50 Dwell Time - 50% reduction of start concentration DVS Deutscher Verband für Schweißen und verwandte Verfahren e.V. (= German Association for Welding and Allied Processes) dw dry weight e.g. EC for example (abbreviation of Latin 'exempli gratia'), for instance European Community ECHA European Chemicals Agency European Economic Area EEA EEC European Economic Community EINECS European Inventory of Existing Commercial Chemical Substances ELINCS European List of Notified Chemical Substances ΕN European Norms EPA United States Environmental Protection Agency (United States of America) ERC **Environmental Release Categories** ES Exposure scenario etc. et cetera European Union FU EWC European Waste Catalogue Fax. Fax number



(GB) Page 10 of 11 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revised on / Version: 16.08.2013 / 0005 Replaces revision of / Version: 13.05.2013 / 0004 Valid from: 16.08.2013 PDF print date: 20.08.2013 Leichtlauf High Tech 5W-40 205 L Art.: 3869 general den. Globally Harmonized System of Classification and Labelling of Chemicals GHS GWP Global warming potential Hen's Egg Test - Chorionallantoic Membrane HET-CAM HGWP Halocarbon Global Warming Potential International Agency for Research on Cancer IARC IATA International Air Transport Association IBC Intermediate Bulk Container IBC (Code) International Bulk Chemical (Code) IC Inhibitory concentration IMDG-code International Maritime Code for Dangerous Goods including, inclusive incl. IUCLID International Uniform ChemicaL Information Database lethal concentration LC lethal concentration 50 percent kill LC50 LCLo lowest published lethal concentration LD Lethal Dose of a chemical LD50 Lethal Dose, 50% kill LDLo Lethal Dose Low LOAEL Lowest Observed Adverse Effect Level LOEC Lowest Observed Effect Concentration LOEL Lowest Observed Effect Level Limited Quantities 10 MARPOL International Convention for the Prevention of Marine Pollution from Ships n.a. not applicable not available n.av. not checked n.c. n.d.a. no data available NIOSH National Institute of Occupational Safety and Health (United States of America) No Observed Adverse Effective Concentration NOAFC NOAEL No Observed Adverse Effect Level NOEC No Observed Effect Concentration NOEL No Observed Effect Level ODP **Ozone Depletion Potential** OECD Organisation for Economic Co-operation and Development org. organic PAH polycyclic aromatic hydrocarbon PBT persistent, bioaccumulative and toxic PC Chemical product category ΡE Polyethylene PNEC Predicted No Effect Concentration POCP Photochemical ozone creation potential parts per million ppm PROC Process category PTFE Polytetrafluorethylene REACH Registration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals) REACH-IT List-No. 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT. RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail) SADT Self-Accelerating Decomposition Temperature Structure Activity Relationship SAR SU Sector of use SVHC Substances of Very High Concern Tel. Telephone ThOD Theoretical oxygen demand TOC Total organic carbon TRGS Technische Regeln für Gefahrstoffe (=Technical Regulations for Hazardous Substances) UN RTDG United Nations Recommendations on the Transport of Dangerous Goods VbF Verordnung über brennbare Flüssigkeiten (= Regulation for flammable liquids (Austria)) VOC Volatile organic compounds vPvB very persistent and very bioaccumulative WEL-TWA. WEL-STEL WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period), WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period) (EH40, UK).



Page 11 of 11 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revised on / Version: 16.08.2013 / 0005 Replaces revision of / Version: 13.05.2013 / 0004 Valid from: 16.08.2013 PDF print date: 20.08.2013 Leichtlauf High Tech 5W-40 205 L Art.: 3869

WHO World Health Organization wwt wet weight

œ

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge. No responsibility.

These statements were made by:

Chemical Check GmbH, Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90

 $^{\odot}$ by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.