Material Safety Data Sheet



Henkel

1. PRODUCT AND COMPANY IDENTIFICATION

Product name: Product type: LOCTITE® 401™ INSTANT ADHESIVE PRISM® Surface Insensitive Cyanoacrylate

IDH number:

135429

Company address: Henkel Corporation One Henkel Way Rocky Hill, Connecticut 06067

Revision Number: 011.1

Item number:40140Region:United StatesContact information:Telephone:860.571.5100MEDICAL EMERGENCY Phone:Poison Control Center1-877-671-4608 (toll free) or 1-303-592-1711TRANSPORT EMERGENCY Phone:CHEMTREC1-800-424-9300 (toll free) or 1-703-527-3887Internet:www.henkelna.com

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW			
Physical state:LiquidColor:ColorlessOdor:Sharp, Irr	, Transparent itating	HMIS: HEALTH: FLAMMABILITY: PHYSICAL HAZARD:	2 2 1
B	OMBUSTIBLE LIQUID ONDS SKIN IN SECON AY CAUSE EYE AND		See MSDS Section 8
Relevant routes of exposure:	Skin, Inhalation, Eyes		
Potential Health Effects			
Inhalation:		e the established exposure limit res eathing and tightness in the chest.	ults in respiratory irritation, which
Skin contact:	Bonds skin in seconds. May cause skin irritation. Cyanoacrylates have been reported to cause allergic reaction but due to rapid polymerization at the skin surface, an allergic response is rare. Cyanoacrylates generate heat on solidification. In rare circumstances a large drop will burn the skin. Cured adhesive does not present a health hazard even if bonded to the skin.		
Eye contact: Ingestion:	Irritating to eyes. Causes excessive tearing. Eyelids may bond. Not expected to be harmful by ingestion. Rapidly polymerizes (solidifies) and bonds in mouth. It is almost impossible to swallow.		
Existing conditions aggravated by exposure:	Eye, skin, and respiratory	disorders.	
	This material is considere 1910.1200).	d hazardous by the OSHA Hazard	Communication Standard (29 CFR

See Section 11 for additional toxicological information.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous components	CAS NUMBER	%
Ethyl 2-cyanoacrylate	7085-85-0	60 - 100
Thickener	Proprietary	5 - 10

	4. FIRST AID MEASURES
Inhalation:	Move to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention.
Skin contact:	Do not pull bonded skin apart. Soak in warm soapy water. Gently peel apa using a blunt instrument. If skin is burned due to the rapid generation of h by a large drop, seek medical attention. If lips are bonded, apply warm wa to the lips and encourage wetting and pressure from saliva in mouth. Peel roll lips apart. Do not pull lips apart with direct opposing force.
Eye contact:	Immediately flush with plenty of water for at least 15 minutes. Get medical attention. If eyelids are bonded closed, release eyelashes with warm wate covering with a wet pad. Do not force eye open. Cyanoacrylate will bond to eye protein and will cause a lachrymatory effect which will help to debond adhesive. Keep eye covered until debonding is complete, usually within 1-days. Medical attention should be sought in case solid particles of polymer cyanoacrylate trapped behind the eyelid caused abrasive damage.
Ingestion:	Ensure breathing passages are not obstructed. The product will polymeriz rapidly and bond to the mouth making it almost impossible to swallow. Sal will separate any solidified product in several hours. Prevent the patient fro swallowing any separated mass.
Notes to physician:	Surgery is not necessary to separate accidentally bonded tissues. Experie has shown that bonded tissues are best treated by passive, non-surgical fi aid. If rapid curing has caused thermal burns they should be treated symptomatically after adhesive is removed.
	5. FIRE FIGHTING MEASURES

5. FIRE FIGHTING MEASURES		
Flash point:	80 - 93.4 °C (176°F - 200.12 °F) Tagliabue closed cup	
Autoignition temperature:	485 °C (905°F)	
Flammable/Explosive limits - lower:	Not determined	
Flammable/Explosive limits - upper:	Not determined	
Extinguishing media:	Water spray (fog), foam, dry chemical or carbon dioxide.	
Special firefighting procedures:	Fire fighters should wear positive pressure self-contained breathing apparatus (SCBA).	
Unusual fire or explosion hazards:	Not available.	
Hazardous combustion products:	Trace amounts of toxic and/or irritating fumes may be released and the use of breathing apparatus is recommended.	

6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions:	Ventilate area. Do not allow product to enter sewer or waterways.
Clean-up methods:	Do not use cloths for mopping up. Flood with water to complete polymerization and scrape off the floor. Cured material can be disposed of as non-hazardous waste.

7. HANDLING AND STORAGE

Handling:

Prevent contact with eyes, skin and clothing. Do not breathe vapor and mist. Wash thoroughly after handling. Avoid contact with fabric or paper goods. Contact with these materials may cause rapid polymerization which can generate smoke and strong irritating vapors, and cause thermal burns.

Storage:

For safe storage, store between 0 °C (32°F) and 10 °C (50°F) Keep in a cool, well ventilated area away from heat, sparks and open flame. Keep container tightly closed until ready for use.

Shelf Life Statement: Not available.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous components	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Ethyl 2-cyanoacrylate	0.2 ppm TWA	None	None	None
Thickener	None	None	None	None
Engineering controls:	Use positive down-draft exhaust ventilation if general ventilation is insufficient to maintain vapor concentration below established exposure limits.			
Respiratory protection:	Use NIOSH approved respirator if there is potential to exceed exposure limit(s).			
Eye/face protection:	Safety goggles or safety glasses with side shields.			
Skin protection:	Use nitrile glove PVC, nylon or		cessary to prevent cont	act. Do not use

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state: Color: Odor: Odor threshold: pH: Vapor pressure: Boiling point/range: Melting point/ range: Specific gravity: Vapor density: Flash point: Flammable/Explosive limits - lower: Flammable/Explosive limits - upper: Autoignition temperature: Evaporation rate: Solubility in water: Partition coefficient (n-octanol/water): **VOC content:**

Liquid Colorless, Transparent Sharp, Irritating 1 - 2 ppm Not applicable < 0.2 mm hg > 149 °C (> 300.2 °F) Not determined 1.05 3 Approximately 80 - 93.4 °C (176°F - 200.12 °F) Tagliabue closed cup Not determined Not determined 485 °C (905°F) Not applicable Polymerises in presence of water. Not applicable < 2 %; < 20 g/l (California SCAQMD Method 316B) (Estimated)

	10. STABILITY AND			
Stability:	Stable under re-	commended storage condition	S.	
Hazardous reactions:		Rapid exothermic polymerization will occur in the presence of water, amines, alkalis and alcohols.		
Hazardous decomposition products	S: Not available.			
Incompatible materials:	Water, amines,	Water, amines, alkalis and alcohols.		
Conditions to avoid:	Spontaneous po	olymerization.		
1	1. TOXICOLOGICAL	INFORMATION		
Acute oral product toxicity:	LD50 (rat) > 5,0	000 mg/kg (Estimated)		
Acute dermal product toxicity:	LD50 (rabbit) >	2,000 mg/kg (Estimated)		
Hazardous components	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated	
Ethyl 2-cyanoacrylate	No	No	No	
Thickener	No	No	No	
lazardous components		Health Effects/Targe	t Organs	
Ethyl 2-cyanoacrylate		Irritant, Allergen, Respiratory		
Thickener		Irritant	-1	
Information provided is for unused product only. Recommended method of disposal: Follow all local, state, federal and provincial regulations for disposal.			gulations for disposal.	
Hazardous waste number:	Not a RCRA ha	zardous waste.		
	14. TRANSPORT INI	FORMATION		
<u>U.S. Department of Transportation (</u> Proper shipping name: Hazard class or division: Identification number: Packing group:		.o.s. (Cyanoacrylate ester)		
International Air Transportation (IC/ Proper shipping name: Hazard class or division: Identification number: Packing group: Exceptions:	Aviation regulated liq 9 UN 3334 III Primary packs contai	uid, n.o.s. (Cyanoacrylate est ining less than 500ml are unre shipped unrestricted.	,	
<u>Water Transportation (IMO/IMDG)</u> Proper shipping name: Hazard class or division: Identification number:	Not regulated None None			

15. REGULATORY INFORMATION

United States Regulatory Information

TSCA 8 (b) Inventory Status:	All components are listed or are exempt from listing on the Toxic Substances Control Act Inventory.	
TSCA 12(b) Export Notification:	None above reporting de minimus	
CERCLA/SARA Section 302 EHS: CERCLA/SARA Section 311/312: CERCLA/SARA 313:	None above reporting de minimis Immediate Health, Delayed Health, Fire, Reactive None above reporting de minimis	
California Proposition 65:	No California Proposition 65 listed chemicals are known to be present.	
Canada Regulatory Information		
CEPA DSL/NDSL Status:	Contains one or more components listed on the Non-Domestic Substances List. All other components are listed on or are exempt from listing on the Domestic Substances List. Components listed on the NDSL must be tracked by all Canadian Importers of Record as required by Environment Canada. They may be imported into Canada in limited quantities. Please contact Regulatory Affairs for additional details.	
WHMIS hazard class:	B.3, D.2.B	
16. OTHER INFORMATION		

This material safety data sheet contains changes from the previous version in sections: Updated Contact Information in Section 1.

Prepared by: Kyra Kozak Woods, Manager, Regulatory Affairs

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.